



### AMP240

240 W Public Address amplifier with 4 Ω/70/100 V output

- Works in 4 Ohms / 70 V / 100 V
  - Safety 24 V
- Adjustable input level
  - 19" rackable
  - High Pass Filter



---

SKU: H9904

Categories: [Amplifiers](#)

### FEATURES

- RMS power : 240 W
- Output levels / Impedance :
  - 100V (42 Ohms)
  - 70V (21 Ohms)
  - 4 Ohms (31V)
- Balanced XLR input
- Balanced XLR output
- Power output on terminals
- 24V DC input on terminal blocks
- Input sensitivity : 01.0V (adjustable)
- Input impedance : 10 KOhms (balanced)
- Frequency response: 70Hz – 18Khz (+/-3 dB)
- T.H.D (1KHz, nominal power): <1%. - Signal to noise ratio: 90 dB - Ground Lift Switch - 400 Hz high-pass filter activated by switch Power supply: - AC 100 - 240V, 50/60Hz - DC24V (safety power supply) - Power consumption: 361 W Protections: - Short circuits - Thermal - Overloading - Dimensions (W x H x D): 482 x 88 x 330 mm - Weight: 13.8 kg - 19 inch rackable - Height: 2 units

## USER MANUALS

Notice FR



Notice EN

