

AMP600

The AMP600 is a 100 V Class D line amplifier (600 W) for fixed installations, combining reliability and high efficiency. It offers a 20 Hz-20 kHz response, THD+N < 0.1% and S/N > 100 dB, with full protection and thermo-regulated ventilation. Euroblock connections, rear volume, HPF, Auto Standby mode (15 min) and 90-264 V PFC power supply. 2U format (483 × 88 × 425 mm), 5.8 kg

SKU: H11708
Categories: 100 V amplifiers, Amplifiers

FEATURES

– Power at 100 V: 600 W
– Output impedance at 100 V: 17 Ohms
– Input sensitivity: 0 dBV/20K Ohms balanced
– Frequency response: 20 Hz – 20 kHz
– THD+N: < 0.1% - S/N: > 100 dB
– Damping factor: > 500 @ 1 kHz
– Power circuit: Class D
– Power supply: PFC switching power supply AC 90-264 V, 50/60 Hz
– Protections: short-circuit, open-circuit, thermal, limiter, ultrasonic and radio frequency
– Connections: input Euroblock GND + – & output Euroblock + -.
– Controls: ON/OFF switch on front panel, volume and HPF on rear panel
– Indicators: Signal, -20 dB, Clip, Protect on front panel
– Cooling: temperature-controlled ventilation
– Dimensions: 483 x 88 x 425 mm (2U, 19-inch)
– Weight: 5.8 kg

USER MANUALS

Guide de l'utilisateur / User guide

⬇ Guide de l'utilisateur / User guide

Gebruikershandleiding

⬇ Gebruikershandleiding

Benutzerhandbuch

⬇ Benutzerhandbuch

Guía del usuario

⬇ Guía del usuario

CE CERTIFICATE

Declaration of conformity

⬇ Français / English

