



## DZ-BOX22

Connection box for microphone or line to be assigned to channels 9/10 or 11/12 of the DZ-MATRIX matrix. Has two balanced analog outputs



SKU: H11396

Categories: [Audio matrix](#)

## FEATURES

### Inputs

Balanced

– Connectors: XLR 3-pin and RCA

– Input impedance: 5.1 K $\Omega$

– THD+N: < 0.01 % typ 20 - 20 kHz, 0 dBu - Maximum input level: 20 dBu - Frequency response: 20 Hz ~ 20 kHz +/- 1.5 dB - Dynamic range: -107 dB max., A-weighting - Crossover distortion: -87 dB max. Weighting A

### Outputs

Balanced

Connectors: 2 x 3-pin, 5 mm pitch

Impedance: 240 Ohms

Maximum output level: +20 dBu

Frequency response: 20 Hz ~ 20 kHz +/- 1.5 dB

Dynamic range: -107 dB max., A-weighted

Crossover distortion: -87 dB max. Weighting A

### Indicators

Signal: -30 dBu, green

Clip: +17 dBu, red

### Ports

RD network to DZ-MATRIX, RJ45, maximum 100 m CAT 5E cable (or higher)

### Dimensions

W x H x D: 147 x 86 x 47 mm

**USER MANUALS**

Presentation EN



EN presentation



DE presentation



Presentation NL



ES presentation



