

DZ-BOX22

Connection box for microphone or line to be assigned to channels 9/10 or 11/12 of the DZ-MATRIX matrix. Has two balanced analog outputs

SKU: H11396
Categories: Audio matrixes, DZ matrices

FEATURES

Inputs
Balanced
– Connectors: XLR 3-pin and RCA
– Input impedance: 5.1 KΩ
– THD+N: < 0.01 % typ 20 - 20 kHz, 0 dBu - Maximum input level: 20 dBu - Frequency response: 20 Hz ~ 20 kHz +/- 1.5 dB - Dynamic range: -107 dB max., A-weighting - Crossover distortion: -87 dB max. Weighting A **Outputs**
Balanced
Connectors: 2 x 3-pin, 5 mm pitch
Impedance: 240 Ohms
Maximum output level: +20 dBu
Frequency response: 20 Hz ~ 20 kHz +/- 1.5 dB
Dynamic range: -107 dB max., A-weighted
Crossover distortion: -87 dB max. Weighting A

Indicators
Signal: -30 dBu, green
Clip: +17 dBu, red

Ports
RD network to DZ-MATRIX, RJ45, maximum 100 m CAT 5E cable (or higher)

Dimensions

W x H x D: 147 x 86 x 47 mm

USER MANUALS

Guide de l'utilisateur

⬇ Guide de l'utilisateur

User guide

⬇ User guide

Gebruikershandleiding

⬇ Gebruikershandleiding

Benutzerhandbuch

⬇ Benutzerhandbuch

CE CERTIFICATE

Declaration of conformity

⬇ Français / English

