




PREZONE642

Mixer 10 inputs and 2-zone preamp

- 2 totally independent zones
- 6 Mic inputs and 4 line inputs
- Level display per zone and per input
- 24 V safety power supply



SKU: H9902

Categories: [Audio mixers](#)

FEATURES

- 6 mono Mic/Line inputs on XLR/Jack
- Phantom power and priority mic on inputs 1 and 2
 - 4 stereo inputs on RCA or Jack
 - Priority input on 6.35 jack
- Zone 1 and 2 mono balanced outputs on XLR
 - Zone insert on 6.35 TRS jack
- Balanced SUB output per zone on jack
 - Stereo REC output on RCA
- Gain and tone control (3 bands) on mic inputs
 - Gain control on stereo inputs
 - Tone control (2 bands) per zone
 - SUB volume control per zone
- Access to dedicated installer settings (via screwdriver)
 - Zone and PFL assignment per input channel
 - Signal and peak display by LED
 - Output level display per zone via 8 LED Vumeter
- Headphone output with volume control (zones and PFL)
 - Power supply: 230 V 50/60 Hz
 - Power consumption: 16 Watts

- DC24 V backup power supply with Link Out
- Frequency response: 20 Hz – 20 kHz (+/- 3dB)
 - H.R.T. (1 kHz nominal power) : $\pm 0.2\%$
 - Equalizer :
 - High: +/-12 dB @ 12.5 kHz
 - Mid : +/-12 dB @ 2,5 kHz
 - Low +/- 12 dB @ 80 Hz
- Dimensions: 295 x 085 x 482 mm
 - 19 inch rackmount
 - Height : 2 units
 - Weight : 5 kg

