



PREZONE8

Analog matrix 8 inputs 8 outputs



SKU: H10927

Categories: [Audio matrix](#)

FEATURES

- Audio outputs: 0 dB (balanced)
 - Input sensitivities
- Announcement microphone input: -50dB +/-3dB (balanced)
 - Remote microphone input: -50dB +/-3dB (balanced)
 - Wall controller mic input: -50dB +/-3dB (balanced)
 - Wall controller line input: -20dB +/-3dB (unbalanced)
 - BGM inputs 1 to 8: -20dB +/-3dB (unbalanced)
- Equalization
 - Bass: 100Hz: +/-12dB +/-1dB
 - Treble: 10KHz: +/-12dB +/-1dB
- T.H.D: Less than 0.05%
- Frequency response
 - Announcement microphone input: 100Hz~10KHz +/- 3 dB
 - Remote microphone input: 100Hz~10KHz +/- 3 dB
 - Wall controller microphone input: 100Hz~10KHz +/- 3 dB
 - Wall controller line input: 60Hz~15KHz +/- 3 dB
 - BGM: 60Hz~15KHz
- Recording capacity: 55 seconds
- Serial interface: Communication speed: 9600 bps
- RS-485: Communication distance: maximum 300m (UTP cat5)
 - Crossover distortion Greater than 75 dB

- Emergency power supply +24 VDC / 350mA
- Power supply: AC 220~240V / 50~60Hz or +24V DC
 - Power consumption: 35 Watts
 - Weight: 5.8 Kg
- Dimensions: 482 x 132 x 315 mm

USER MANUALS

Notice FR / EN



Notice NL



Notice DE



Notice ES



